

GET YOUR SAVINGS UP FRONT!



STOLL LOADLINE Front Loader systems are the only front loader system to be approved by NEW HOLLAND for installation on the new TS A tractor range.

Offering a comprehensive selection of loader specifications (4 different loader models), and a choice of:

- Non-Self levelling (HD)
- Mechanical Self levelling (HDPM) or
- Hydraulic Self levelling (HDP) lift booms

Providing a STOLL loader model to suit all needs.



New tractor brackets are designed using the latest CAD programs resulting with brackets that work in harmony with the tractor design.

A choice of either factory or retro fit brackets are available. Tractor brackets and single lever can be fitted on the tractor production line, or the retro fit brackets can be supplied to fit onto stock or existing tractors.

The standard specification of the Retro-fit system includes; loader boom, electric 3rd service, tractor brackets, radiator guards & joystick control.

The joystick control system supplied with the Retro-fit system comes as standard with a rotating mounting bracket.

This allows the operator when not using the loader, to rotate the lever towards the front window, gaining easy access to the cab from the right side door. When in use the single lever is positioned between the steering wheel and the right hand console.



NEW HOLLAND TS A

The **STOLL Loadline Front loader system** offers a wide range of options to complement the standard specification of the loader booms, with many operator and servicing advantages.

Standard specification include:

- Electric 3rd service to operate Silage grabs e.t.c
- Narrow profile loader arm with 1 oval cross beam for improved visibility
- All pivot points are greased from the outside of the lift arm, for easy access
- DX bushes used on all pivot points, ensuring that grease is retained around the bush
- No tools required to remove the loader from the tractor or to re-mount
- Self adjusting stand legs
- Tool locking and un-locking with one handle operated from left side of tractor (Automatic locking as standard).

OPTIONS:

Hydro-Fix

(Connection of all hydraulic pipes between tractor brackets and the loader boom with 1 movement of a handle)



3rd Service Hydro-Fix
(Connection of 2 hydraulic pipes between loader boom and an attachment)

Comfort Drive (Hydraulic ram suspension, increasing operator comfort by absorbing the shock effects when in work or transport)



EHS PRO Display

(Programmable Proportional Single lever System, with digital display)



Hydro-Lock (Hydraulic tool locking)

Electric 4th Service

Choice of Loader attachment Headstocks



Mono-Weight 650 or 1100kg
(Rear ballast mounted on linkage arms)

Wide range of loader attachments.



For further information on the Robust F loader systems and attachments please refer to the STOLL Brochure.

Robust F HDPM	10	15	30	35
Q1 (kg)	2050	2532	2310	2652
Q2 (Kg)	1474	1821	1688	1938
N1 (Kg)	1850	2332	2110	2452
N2 (Kg)	1274	1621	1488	1738
R (Kg)	2288	2780	2281	2782
H (mm)	3755	3755	4084	4084
L (mm)	3545	3545	3874	3874
A (mm)	2860	2860	3192	3192
W (mm)	628	628	785	785
S (mm)	210	210	210	210

A - Robust F 10 & 15
B - Robust F 30 & 35

The above figures are for Mechanical Self Levelling loaders, the lift capacity figures do vary for the Non Self levelling & Hydraulic Self levelling models (Please refer to the STOLL brochure for accurate figures)